



Skyfol[®]
Film Solutions

PPF_{Wrap} AC
paint protection film

Discover our latest series of dry-install paint protection films, the **Skyfol PPF Wrap AC**, characterized by exceptional flexibility, ease, and speed of installation. There is no need to worry about repositioning or squeegee lines; the dry installation technique guarantees a hassle-free application. This series is made from 100% polyurethane film, available in a wide range of colors directly from our stock. Experience the perfect protection and irresistible satin finish provided by the Skyfol PPF Wrap AC.



**Real PPF
level protection**



**More durable than
PVC car wrap films**



**Anti-scratch
coating**



**Easily accessible
from stock**



Dry install




Unique style

RAW MATERIAL:

Skyfol PPF Wrap AC is a biodegradable, polyester-based aliphatic thermo polyurethane film. As it is resistant to orange peel, yellowing and UV, it is widely used for the exterior surface protection of vehicles.

STRUCTURE OF THE FILM:





Skyfol[®]
Film Solutions

PPF_{Wrap} AC
paint protection film

TECHNICAL FEATURES:

Thickness:	200 micron
Elongation at break:	>300
Adhesive:	Removable, repositionable, non-yellowing acrylic adhesive.
Adhesive initial tack:	$16 \leq F \leq 26$
Adhesive holding tack:	$20 \leq F \leq 30$
Resistance:	The film is resistant to general-use automotive fuels.
Shelf life:	1 year, stored optimally at 22°C and with relative humidity 50%.

TECHNICAL SPECIFICATIONS:

technical data, recommendations, and other statements contained in this document are based on tests and experimental data that we believe to be reliable but whose accuracy and completeness are not guaranteed.

PRODUCT USE:

in actual use, many of the factors beyond the control of Skyfol can affect the performance of the product. Due to the diversity of factors affecting product performance, it is entirely the responsibility of the user to make sure that the film is suitable for the actual use.

PRODUCT SAFETY:

the product is a urethane film with residual solvent odour, but it does not release hazardous chemicals under normal use.

LIMITATION OF LIABILITY:

with the exception of statutory prohibitions, Skyfol shall not be held liable for any direct, indirect, special or incidental loss or damage related to the Skyfol product, regardless of any legal, statutory (warranty, contract), negligence or objective liability.

WARRANTY:

The installer assumes a 5-year warranty on the installation.

The warranty applies to the film getting detached from the surface due to adhesive failure, cracking and bubbling. The warranty period begins on the date of the invoice is sued for the installation. The warranty applies only if in stallation is carried out on the original factory paintwork. The warranty is non-transferable and applies only to the original customer. In case of problems due to material defects, Skyfol undertakes to replace the material. The value of the claim shall not exceed the gross purchase price indicated on the invoice for the sale of the product. The warranty does not cover damage caused by improper use, accidents, improper installation and normal wear and tear of the product, neither dents caused by stones and road debris. The paint protection film can be ordered from official Skyfol distributors published at www.skyfol.com. Always consult the relevant Skyfol representatives who will inform you about roll sizes, minimum order quantities, prices and other business terms.

CONTACT:

For the selection of the material and to receive technical assistance for application, visit our website at www.skyfol.com